

## Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: P0022  
Product name: SILSAN COLOR BIANCO

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Rivestimento acril-silossanico per pareti

#### 1.3. Details of the supplier of the safety data sheet

Name: Licata S.p.A.  
Full address: Via De Gasperi,155  
District and Country: 92024 Canicatti (AG)  
Italia  
Tel.: +39 0922 856088  
Fax: +39 0922 831427

e-mail address of the competent person responsible for the Safety Data Sheet: controllo.qualita@licataspa.it

#### 1.4. Emergency telephone number

For urgent inquiries refer to: + 39 0922 856088

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Hazardous to the aquatic environment, chronic toxicity, category 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:  
P273 Avoid release to the environment.

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

**P0022 - SILSAN COLOR BIANCO****SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>ETHANEDIOL</b>		
INDEX 603-027-00-1	0,6 ≤ x < 0,7	<b>Acute Tox. 4 H302 STA Oral: 500 mg/kg</b>
EC 203-473-3		
CAS 107-21-1		
<b>3-(4-Isopropylphenyl)-1,1-dimethylurea</b>		
INDEX 006-044-00-7	0,025 ≤ x < 0,08	<b>Carc. 2 H351, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=10</b>
EC 251-835-4		
CAS 34123-59-6		
<b>Trimethylolpropane</b>		
INDEX	0 ≤ x < 0,05	<b>EUH066, EUH210, EUH212</b>
EC 201-074-9		
CAS 77-99-6		
REACH Reg. 01-2119486799-10-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures****4.1. Description of first aid measures**

Not specifically necessary. Observance of good industrial hygiene is recommended.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

Choose the most appropriate extinguishing equipment for the specific case.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

**5.2. Special hazards arising from the substance or mixture**

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

The product is neither flammable nor combustible.

**5.3. Advice for firefighters**

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Use breathing equipment if fumes or powders are released into the air. These indications apply for both processing staff and those involved in emergency procedures.

**P0022 - SILSAN COLOR BIANCO****SECTION 6. Accidental release measures ... / >>****6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

**7.2. Conditions for safe storage, including any incompatibilities**

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

**ETHANEDIOL****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	26	10	52	20	SKIN
MAK	DEU	26	10	52	20	SKIN
VLA	ESP	52	20	104	40	SKIN
VLEP	FRA	52	20	104	40	SKIN
GVI/KGVI	HRV	52	20	104	40	SKIN
VLEP	ITA	52	20	104	40	SKIN
MV	SVN	52	20	104	40	SKIN
WEL	GBR	52	20	104	40	SKIN
OEL	EU	52	20	104	40	SKIN
TLV-ACGIH			25		50	
TLV-ACGIH				10		INHAL

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

**P0022 - SILSAN COLOR BIANCO****SECTION 8. Exposure controls/personal protection ... / >>****8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

**HAND PROTECTION**

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	dense liquid	
Colour	various	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	incombustible	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	9-10	
Kinematic viscosity	not available	
Solubility	miscible	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	not available	
Relative vapour density	not available	
Particle characteristics	not applicable	

**9.2. Other information**

## 9.2.1. Information with regard to physical hazard classes

**Flammable liquids**

Sustained combustibility does not sustain combustion

## 9.2.2. Other safety characteristics

**P0022 - SILSAN COLOR BIANCO**

Information not available

**SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

ETHANEDIOL

In the air absorbs moisture. Decomposes at temperatures above 200°C/392°F.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHANEDIOL

Risk of explosion on contact with: perchloric acid. May react dangerously with: chlorosulphuric acid, sodium hydroxide, sulphuric acid, phosphorus pentasulphide, chromium (III) oxide, chromyl chloride, potassium perchlorate, potassium dichromate, sodium peroxide, aluminium. Forms explosive mixtures with: air.

**10.4. Conditions to avoid**

None in particular. However the usual precautions used for chemical products should be respected.

ETHANEDIOL

Avoid exposure to: sources of heat, naked flames.

**10.5. Incompatible materials**

Information not available

**10.6. Hazardous decomposition products**

ETHANEDIOL

May develop: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, carbon monoxide, hydrogen.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

ETHANEDIOL

WORKERS: inhalation; contact with the skin.

POPULATION: inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

ETHANEDIOL

Ingestion initially stimulates the central nervous system; later replaced by a phase of depression. There may be kidney damage, with anuria and uremia. Over-exposure symptoms are: vomiting, drowsiness, difficulty in breathing, convulsions. The lethal dose for humans is approx. 1.4 ml/kg.

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

**P0022 - SILSAN COLOR BIANCO****SECTION 11. Toxicological information ... / >>**

ATE (Dermal) of the mixture: Not classified (no significant component)

ETHANEDIOL  
LD50 (Dermal): 9530 mg/kg Rabbit  
LD50 (Oral): > 2000 mg/kg Rat

TITANIUM DIOXIDE  
LD50 (Oral): > 10000 mg/kg Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

ETHANEDIOL  
Available studies have shown no carcinogenic potential. In a carcinogenicity study lasting two years, carried out by the US National Toxicology Program (NTP), in which ethylene glycol was administered in the feed, "no evidence of carcinogenic activity" in male and female B6C3F1 mice was observed (NTP, 1993).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**SECTION 12. Ecological information**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

**12.1. Toxicity**

Information not available

**12.2. Persistence and degradability**

**P0022 - SILSAN COLOR BIANCO****SECTION 12. Ecological information** ... / >>

ETHANEDIOL  
Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

TITANIUM DIOXIDE  
Solubility in water < 0,001 mg/l  
Degradability: information not available

**12.3. Bioaccumulative potential**

ETHANEDIOL  
Partition coefficient: n-octanol/water -1,36

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

**14.1. UN number or ID number**

not applicable

**14.2. UN proper shipping name**

not applicable

**14.3. Transport hazard class(es)**

not applicable

**14.4. Packing group**

not applicable

**P0022 - SILSAN COLOR BIANCO****SECTION 14. Transport information ... / >>****14.5. Environmental hazards**

not applicable

**14.6. Special precautions for user**

not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: \_\_\_\_\_ None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product	
Point	3
Contained substance	
Point	75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors  
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Carc. 2</b>	Carcinogenicity, category 2
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H351</b>	Suspected of causing cancer.
<b>H302</b>	Harmful if swallowed.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.
<b>EUH210</b>	Safety data sheet available on request.
<b>EUH212</b>	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.



**P0022 - SILSAN COLOR BIANCO****SECTION 16. Other information ... / >>****LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the

**P0022 - SILSAN COLOR BIANCO**

suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.